

EQUIPMENT WIRE

PVC Insulated Equipment Wire

Generally to Defence Standard 61-12 Part 2 and 3 and BS4808

MASON Part No.	Type	Conductor Size (mm ²)	No. & Size Of Wires	Mean Radial Insulation Thickness	Maximum O.D.
DEF0722	2	0.22	7 x 0.20 mm	0.30 mm	1.30 mm
DEF1622	2	0.50	16 x 0.20 mm	0.30 mm	1.65 mm
DEF2422	2	0.75	24 x 0.20 mm	0.45 mm	2.15 mm
DEF3223	3	1.00	32 x 0.20 mm	0.60 mm	2.65 mm

APPLICATION

PVC insulated equipment wire is used for the internal wiring of electrical and electronic equipment.

SPECIFICATION

DEF.STAN. 61-12 Part 6 Types 2 & 3 .BS4808

Voltage Rating: Type 2, 1000 volt

Type 3, 1500 volt

Tinned annealed copper conductors PVC insulated

Maximum temperature 85 °C

STANDARD COLOURS

Black, Blue, Brown, Green, Grey, Orange, Pink, Red, Violet, White, Yellow, Green / Yellow

Other two and three colour options are available upon request

Please contact our Sales Office for details of colours available in particular sizes / lengths

PACKAGING

Supplied on 500M and 1000M reels depending on conductor size / colour