

## HOOK UP WIRE

### PVC Insulated UL Hook Up Wire

To UL Style 1007/1569 & CSA Type TR-64



MASON Part No.	AWG	No. & Size of Strands	Nominal Insulation Thickness	Nominal O.D.	Nominal D.C. Resistance at 20°C	Reel Size
UL100728	28	7 x 0.12 mm	0.38 mm	1.25 mm	238.90 Ω/km	1000m
UL100726	26	7 x 0.16 mm	0.38 mm	1.30 mm	148.94 Ω/km	1000m
UL100724	24	11 x 0.16 mm	0.38 mm	1.50 mm	93.25 Ω/km	1000m
UL100722	22	17 x 0.16 mm	0.38 mm	1.60 mm	55.00 Ω/km	1000m
UL100720	20	10 x 0.25 mm	0.38 mm	1.80 mm	40.02 Ω/km	1000m
UL100718	18	16 x 0.25 mm	0.38 mm	2.10 mm	21.80 Ω/km	500m

To UL Style 1061 & CSA Type AWM

MASON Part No.	AWG	No. & Size of Strands	Nominal Insulation Thickness	Nominal O.D.	Nominal D.C. Resistance at 20°C	Reel Size
UL106128	28	7 x 0.12 mm	0.26 mm	0.90 mm	238.90 Ω/km	1000m
UL106126	26	7 x 0.16 mm	0.26 mm	1.00 mm	139.00 Ω/km	1000m
UL106124	24	7 x 0.20 mm	0.27 mm	1.15 mm	93.25 Ω/km	1000m
UL106122	22	7 x 0.25 mm	0.26 mm	1.28 mm	55.00 Ω/km	1000m

### APPLICATION

Stranded UL and CSA certified Hook Up Wire is used for the internal wiring of electrical and electronic equipment.

### SPECIFICATION

Voltage rating 300 volts

Tinned annealed copper conductors

Insulated with heat resistant PVC

Conforms with the UL VW-1 vertical wire flame test

Maximum temperature 105 °C

### STANDARD COLOURS

Black, Blue, Brown, Green, Grey, Orange, Pink, Red, Violet, White, Yellow, Green / Yellow

Other two and three colour options are available upon request

Please contact our Sales Office for details of colours available in particular sizes / lengths