MASON CABLES & ACCESSORIES LTD
Tel : (0121) 585 8900 www.masoncables.co.uk Fax : (0121) 585 9900

PVC / PVC FLEXIBLE CORDS

PVC / PVC Flexible Cords

To BS6500

MASON Part No.	Type	Harmonised Code	Cross Sectional Area (mm^2)	Nominal O.D.	Weight (kg / km)
2192Y050	2192Y	H03VVH2-F	2 x 0.50	3.3mm x 5.4mm oval	28
2182Y050	2182Y	H03VV-F	2 x 0.50	5.4 mm	36
2183Y050	2183Y	H03VV-F	3 x 0.50	5.6 mm	44
3182Y075	3182Y	H05VV-F	2 x 0.75	6.8 mm	63
3183Y075	3183Y	H05VV-F	3 x 0.75	6.8 mm	75
3184Y075	3184Y	H05VV-F	4 x 0.75	7.7 mm	78
3182Y100	3182Y	HO5VV-F	2 x 1.00	7.2 mm	73
3183Y100	3183Y	HO5VV-F	3 x 1.00	7.2 mm	86
3184Y100	3184Y	HO5VV-F	4 x 1.00	8.5 mm	110
3183Y150	3183Y	HO5VV-F	3 x 1.50	8.2 mm	120
3184Y150	3184Y	HO5VV-F	4 x 1.50	10.0 mm	150

APPLICATION

A flexible mains cable for internal use in the direct connection of electrical equipment to mains power supplies.

SPECIFICATION

BS6500

Voltage Rating: 219-Y / 218-Y 300 / 300 volt

318-Y 300 / 500 volt

Plain annealed copper conductors

PVC insulated PVC sheathed flexible mains cable

Maximum temperature 60 °C

PACKAGING
Supplied on
100 metre reels

STANDARD COLOURS

Core Colours 2 core : Brown, Blue

3 core : Brown, Blue, Green/Yellow

4 core : Brown, Grey, Black, Green/Yellow

Sheath Colours: Black, White